



## *2400 Acrylic Brush Grade*

### ***PRODUCT DATA***

*2400 is formulated to adhere to any clean surface. 2400 is designed to seal the joints between masonry, brick, metal, wood and glass. 2400 brush grade is also used to repair hair-line cracks in stucco and other masonry surfaces.*

*2400 is available in white only.*

***Application:*** *can be brushed, rolled or sprayed. Final thickness of 2400 will vary depending on surface conditions. Allow four to eight hours between coats. Dry time will vary with the thickness of the application.*

*2400 is available in 1 and 5 gallon plastic containers.*

*For more detailed instructions refer to our Installation Guide or consult ACRYLABS, INC. technical department.*



## **ACRYLIC COATINGS**

# **2400 TECHNICAL DATA**

### **TYPICAL PROPERTIES**

<b>WEIGHT PER GALLON</b>	<b>11.7 LBS.</b>
<b>% SOLIDS BY WEIGHT</b>	<b>70.5</b>
<b>% SOLIDS BY VOLUME</b>	<b>57.8</b>
<b>VISCOSITY: CENTIPOSIES AT 77 DEGREES BROOKFIELD (HBT)</b>	<b>60000 +- 5000</b>
<b>RHEOLOGICAL CHARACTERISTICS</b>	<b>THIXOTROPIC</b>
<b>CONSISTENCY</b>	<b>BRUSHABLE PASTE</b>
<b>FLASH POINT</b>	<b>N/A</b>
<b>LOW TEMPERATURE FLEXABILITY</b>	<b>ASTM D-746</b>
<b>SERVICE TEMPERATURE RANGE</b>	<b>-30F TO 180F</b>
<b>SHELF LIFE</b>	<b>2 YEAR MINIMUM</b>
<b>VEHICLE TYPE</b>	<b>ELASTOMERIC</b>
<b>V.O.C. CONTENT</b>	<b>82.4 g/l (0.66 lbs./gal)</b>

**AcryLabs, 730 Commercial Lane, Honeybrook, PA 19344**

**Phone 610-273-1355, Fax 610-273-1357**

**[www.acrylabs.com](http://www.acrylabs.com)**