



## ACRYLIC COATINGS

### 3100 EPDM/Single Ply Primer

**3100** is a high quality, EPDM/Single Ply primer that is formulated to promote maximum adhesion. **3100** is a high pH, rinseable primer that can be used to clean most surfaces. Although **3100** is not harmful to the environment, proper care should be taken during application. Protective eyewear and gloves must be used. Surfaces treated with the **3100** can be extremely slippery when wet. Always use fall protection when working on roofs.

**Application:** can be brushed, rolled or sprayed. Application rate (approximately 500 Sq. Ft. Per gallon) will vary with the porosity of the surface. Allow ten to fifteen minutes to activate before power washing, with a minimum of 2000psi. The surface should be clean and dry before the installation of an AcryLabs System. Dry time will vary depending on temperature, humidity and ventilation.

**3100** is available in 1 and 5 gallon plastic containers.

AcryLabs, 730 Commercial Lane, Honey Brook, PA 19344

Phone 610-273-1355, Fax 610-273-1357

[www.acrylabs.com](http://www.acrylabs.com)



## **ACRYLIC COATINGS**

### *3100 Technical Data*

#### ***TYPICAL PROPERTIES***

<b><i>APPEARANCE</i></b>	<b><i>Clear pink liquid</i></b>
<b><i>WEIGHT PER GALLON</i></b>	<b><i>Approx. 8.3 Lbs.</i></b>
<b><i>PH</i></b>	<b><i>13.0 – 13.5</i></b>
<b><i>VISCOSITY</i></b>	<b><i>Same as Water</i></b>

#### ***Wet adhesion of 2100B and 2100 to EPDM Membrane***

<b><u>Preparation</u></b>	<b><u>Wet adhesion (pli)</u></b>
<b>None</b>	<b>.7</b>
<b>Power wash/water</b>	<b>.7</b>
<b>Prepared with 3100 Primer</b>	<b>1.8</b>

**AcryLabs, 730 Commercial Lane, Honey Brook, PA 19344**  
**Phone 610-273-1355, Fax 610-273-1357**

[www.acrylabs.com](http://www.acrylabs.com)