



## **ACRYLIC COATINGS**

# *3200 Acrylic Rust Inhibitive Primer*

### ***PRODUCT DATA***

**3200** is a water born acrylic direct-to-metal (DTM) coating for the construction market. Utilizing advanced technology the **3200** is formulated for maximum adhesion to metals and masonry.

**3200** cures to a strong durable finish that is easily maintained. **3200** is the recommended coating/primer for most corroded metal walls and roofs.

**3200** is available in Red.

**Application:** can be brushed, rolled or sprayed. Final thickness of **3200** will vary depending on surface conditions. **3200** should be applied at 300 square feet per gallon to achieve the suggested dry film thickness of 2 - 3 mils (DFT). Allow two to four hours between coats, dry time will vary depending on temperature, humidity and ventilation.

**3200** is available in 1 and 5 gallon plastic containers.

For more detailed instructions refer to our Installation Guide or consult ACRYLABS, INC. technical department.



## **ACRYLIC COATINGS**

### **3200 TECHNICAL DATA**

#### ***TYPICAL PROPERTIES***

<b>WEIGHT PER GALLON</b>	<b>11.8 LBS.</b>
<b>FINISH</b>	<b>FLAT</b>
<b>V.O.C.</b>	<b>0.76 lbs./gal (91g/l)</b>
<b>SOLIDS BY VOLUME</b>	<b>44%</b>
<b>SERVICE TEMPERATURE LIMIT</b>	<b>200F</b>
<b>FLAME SPREAD RATING</b>	<b>CLASS "A" (0-25) OVER Noncombustable Surfaces</b>
<b>FLASH POINT</b>	<b>N/A</b>
<b>SHELF LIFE</b>	<b>1 YEAR</b>
<b>CLEAN UP</b>	<b>SOAP &amp; WATER</b>

**AcryLabs, 730 Commercial Lane, Honey Brook, PA 19344**  
**Phone 610-273-1355, Fax 610-273-1357**

**[www.acrylabs.com](http://www.acrylabs.com)**