



Liquid Roofing Products

Acrypel

PRODUCT DATA

Description: Acrylabs **Acrypel** is a high quality, silane/siloxane based acrylic water repellent that is formulated for maximum durability and adhesion. **Acrypel** can be applied to new or restored surfaces, high porosity concrete, split face block, brick, adobe, limestone, granite, sandstone, terracotta, stucco & mortar. **Acrypel** is an excellent block sealer and can be used on most vertical or horizontal exterior and above grade masonry surfaces. **Acrypel** performs well in a variety of climates and temperatures. **Acrypel** is environmentally friendly and safe for plants and animals.

Application: **Acrypel** is best applied using a hand held garden pump sprayer using a flood coat technique from the bottom up. Application rate will vary with the porosity of the surface.

Coverage: Approximately 50-100 SF per gallon depending on surface porosity.

Acrypel is available in 1 and 5 gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	7.84 LBS
FINISH	CLEAR
VISCOSITY	SIMILAR TO WATER
V.O.C.	50.6g/l (.422 # / gallon)
SOLIDS BY VOLUME	10%
SERVICE TEMPERATURE LIMIT	N/A
FLASH POINT	NONE
SHELF LIFE	1 YEAR
CLEAN UP	SOAP & WATER

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.

Corporate Offices: 101 N. Prospect Street, Reading, PA 19606 · (866) 273-1355