

PRODUCT DATA & TECHNICAL DATA



Liquid Roofing Products

Rinse Prep



SDS

DESCRIPTION AcryLabs Rinse Prep is an easy to use and water based EPDM cleaner that is formulated to promote maximum adhesion of A.L.A.R.M. - *Systems*. It is used to remove the oxidized carbon black from the EPDM surface and can also be used on other existing roof surfaces that require a cleaning.

APPLICATION Rinse Prep can be sprayed using a pump type garden sprayer. Application rate (approximately 500 SF per gallon) will vary with the condition of the surface. Allow ten to fifteen minutes to activate before power washing, with a minimum of 3000 psi.

SURFACE PREP Surface must be clear of all loose or collected contaminants.

PACKAGING Rinse Prep is available in 1 and 5 gallon plastic containers.

COVERAGE Rinse Prep will yield approximately 500 SF per gallon.

DRYING TIME Varies depending on weather factors. Wait at least 10-15 minutes or until dry, then power wash surface clean.

CLEAN-UP Water

WARRANTY Limited to replacement of product.

PROPERTY	RESULT	TEST METHOD
VISCOSITY	Same as water	ASTM D-562-01
PH	13 - 13.5	ASTM E-70-97
WEIGHT PER GALLON	8.3 LBS	ASTM D-1475

Meets and exceeds ASTM D6083 requirements.



Corporate Offices: 101 North Prospect Street, Reading, PA 19606 • (866) 273-1355