



Liquid Roofing Products

Metal Prep Rust Inhibitive Primer

PRODUCT DATA

Description: Acrylabs **Metal Prep** is a single component water based, highly effective acrylic coating used to address rusted metal. The **Metal Prep** formulation is engineered for maximum adhesion to all types of rusty metal and provides excellent surface corrosion protection and prevents rust bleed through prior to application of Acrylabs **Liquid Applied Roof Membrane - Systems**.

Application: **Metal Prep** can be brush, roll or spray applied. **Metal Prep** should be applied at 150-200 SF per gallon to achieve the suggested dry film thickness of 2-3 mils (DFT). It can also be used to spot prime rust as needed.

Rust Inhibitive Primer is available in 1 and 5 gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	10.8 LBS.
FINISH	Low Sheen
V.O.C.	<0.83 lbs./gal (100g/l)
SOLIDS BY VOLUME	39%
SERVICE TEMPERATURE LIMIT	180 F
FLAME SPREAD RATING	N/A
FLASH POINT	200 F, Seta Flash
SHELF LIFE	1 YEAR
CLEAN UP	SOAP & WATER

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.

Corporate Offices: 101 N. Prospect Street, Reading, PA 19606 · (866) 273-1355