



Liquid Roofing Products

Finish Coat

PRODUCT DATA

Description: **Acrylabs Finish Coat** is a water based, 100% acrylic elastomeric product and is a component of the **Acrylabs Liquid Applied Roof Membrane - Systems**. The **Finish Coat** formulation is engineered for maximum adhesion to new surfaces, such as concrete, plywood, OSB, EPS, fiberglass, cement board, and existing surfaces such as asphalt, BUR, modified bitumen, EPDM, single ply membrane systems and metal. **Finish Coat** cures to a strong, durable finish that is easily maintained and is used as the final coats for the Acrylabs Roof Systems. **Finish Coat** is an excellent product when used as a wall coating. The heavy bodied formulation fills minor cracks and voids and creates an exterior skin helping create a air and moisture barrier.

Finish Coat is available in other colors.

Application: **Finish Coat** can be brush, roll or spray applied. Two coats are required to maintain a pinhole free membrane. Allow to dry before recoating. For best results apply **Finish Coat** when the surface temperature is 40F and rising.

Finish Coat is available in 5 and 55 gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	12 LBS	ASTM D-1475
% SOLIDS BY WEIGHT	67.0%	ASTM D-1644-A
% SOLIDS BY VOLUME	53%	ASTM D-2697
PIGMENT VOLUME	43.0%	
VISCOSITY (Brookfield)	130-140 Ku	ASTM D-562-A
V.O.C.	<50 g/l	ASTM D3960-01
PH	8.6 -9.2	ASTM E70-97
FLASH POINT	N/A	
LOW TEMPERATURE FLEXIBILITY	Mandrel Bend @ -49F	ASTM D522-93A
ELONGATION AT (break)	196% @ 73F	ASTM D-2370
TENSILE STRENGTH AT (psi)	236psi @ 73F	ASTM D-2370
WATER SWELLING	9.2	ASTM-D 471
FUNGI RESISTANCE	ZERO RATING	G-53
PERMEABILITY (20MILS)	21.9 PERMS	ASTM D1653
ACCELERATED WEATHERING	NO EFFECT 2 YEARS	ASTM G-53

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.

Corporate Offices: 101 N. Prospect Street, Reading, PA 19606 · (866) 273-1355