



Liquid Roofing Products

Brushable Sealant

PRODUCT DATA

Description: Brushable Sealant is a water based, 100% acrylic formulation similar to Acrylabs coatings but enhanced to be heavier bodied and contains Kevlar reinforcement.

Brushable Sealant is formulated to adhere to clean surfaces and is designed to address seams and fasteners on metal roofs. Can also be used to smooth irregular surfaces, fill joints, cracks and imperfections on existing deck surfaces.

Application: Brushable Sealant can be brushed or troweled on. Allow to dry between coats if multiple applications are required to build up a surface. Dry time will vary with the thickness of the application.

Brushable Sealant is only available in Gray. **Brushable Sealant** is available in 1 and 5 gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	11.1 LBS	ASTM D1475-90
% SOLIDS BY WEIGHT	59.0	ASTM D2369-97
% SOLIDS BY VOLUME	52	ASTM D2697
PIGMENT VOLUME	43.0%	
VISCOSITY	248,000 cps	ASTM D562-01
V.O.C.	<50 g/l	ASTM D3960-01
PH	9.0 -9.6	ASTM E70-97
FLASH POINT	N/A	
TYPICAL PROPERTIES (20 mil DFT)		
FUNGUS GROWTH	NONE	
ACCELERATED WEATHERING	NO EFFECT 2 YEARS	ASTM E96-80
LOW TEMPERATURE FLEXIBILITY	Mandrel bend @ -49F	ASTM D522
ELONGATION AT BREAK	195%	ASTM D-412
TENSILE STRENGTH AT BREAK	433psi	ASTM D-412
PERMEABILITY (20MILS)	<10 PERMS	ASTM E96-80
OZONE DEGRADATION	NO EFFECT	ASTM D-1149

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.

Corporate Offices: 101 N. Prospect Street, Reading, PA 19606 · (866) 273-1355