

PRODUCT DATA & TECHNICAL DATA



Liquid Roofing Products

NewClear



SDS

DESCRIPTION AcryLabs NewClear is a water based, 100% clear acrylic elastomeric coating used for sealing and renewing acrylic and fiberglass skylights. NewClear cures to a strong, durable finish that is easily maintained.

APPLICATION NewClear can be brush, roll or spray applied. Two coats are always required. When rolling or spraying, back-brush immediately to avoid streaking. Do not apply when temperature is below 50°F.

SURFACE PREP Substrate should be clean and dry. Avoid applying in direct sunlight or when surface temperatures are extremely hot.

PACKAGING NewClear is available in 1 and 5 gallon plastic containers.

COVERAGE 250 SF per gallon will yield approximately 3 mils per coat. Two coats are recommended.

DRYING TIME Varies depending on weather factors. Recommended to accept foot traffic before re-coating.

CLEAN-UP Water

WARRANTY Limited to replacement of product.

PROPERTY	RESULT	TEST METHOD
% SOLIDS BY VOLUME	50 ± 2%	ASTM D-1653
VOC	50.6 g Liter	ASTM D-3960-01
VISCOSITY	Low	ASTM D-562-01
FLASHPOINT	None	
WEIGHT PER GALLON	7.84 LBS	ASTM D-1475

Meets and exceeds ASTM D6083 requirements.



Corporate Offices: 101 North Prospect Street, Reading, PA 19606 • (866) 273-1355