



Roof Membrane Care and Maintenance

Acrylabs Liquid Applied Roof Membrane-Systems are easily maintained with periodic cleaning and inspections.

Periodic cleaning of the membrane and removal of accumulated debris will keep the surface looking attractive and ensure its longevity. Prolonged periods of trapped moisture will foster the growth of mildew and fungus which could degrade the surface. Soap and water, mild detergents, TSP, diluted bleach solution or environmentally responsible outdoor cleaning agents are all suitable for use on the membrane. Avoid using cleaners containing abrasives.

Ensure that objects placed on the roof will continue to allow the surface to drain water easily.

Use a plastic shovel to remove snow. Salt or other snow melting products can be used to remove ice from the roof.

The Acrylabs Liquid Applied Roof Membrane System can be refreshed and renewed at any point during the warranty period. Consult Acrylabs application guidelines for re-coating procedures and requirements.

In most cases, re-coating at the end of the warranty period will renew the warranty as well as the roof surface.

In case of damage, Acrylabs membranes are easily repaired with the application of Acrylabs Products. Report all damage to Acrylabs Corporate Office.

In order to maintain Acrylabs Warranties, all applications of the Acrylabs Liquid Applied Roof Membrane Systems and its repairs must be performed by an Acrylabs Approved Applicator or other persons authorized by Acrylabs.

Consult Acrylabs Corporate Offices with any questions or concerns not covered in this outline.

Corporate Offices: 101 North Prospect Street, Reading, PA 19606 • (866) 273-1355

