

# PRODUCT DATA & TECHNICAL DATA



Liquid Roofing Products

## Brushable Sealant



SDS

**DESCRIPTION** Brushable Sealant is a water based, 100% acrylic formulation similar to AcryLabs coatings but enhanced to be heavier bodied and contains Kevlar reinforcement. Brushable Sealant is formulated to adhere to clean surfaces and is designed to address seams and fasteners on metal roofs. Brushable Sealant can also be used to smooth irregular surfaces, fill joints, cracks and imperfections on existing deck surfaces.

**APPLICATION** Brushable Sealant can be brushed or troweled on. Allow to dry between coats if multiple applications are required to build up a surface. Dry time will vary with the thickness of the application.

**SURFACE PREP** Substrate should be clean and dry. Rusty metal surfaces require AcryLabs Metal Prep.

**PACKAGING** Brushable Sealant is available in 1 and 5 gallon plastic containers.

**COVERAGE** Seams - 150 LF per 1 gallon and Fasteners - 300 count per 1 gallon.

**DRYING TIME** Varies depending on weather factors. Recommended to accept foot traffic before re-coating.

**CLEAN-UP** Water

**WARRANTY** Limited to replacement of product.

PROPERTY	RESULT	TEST METHOD
% SOLIDS BY VOLUME	53.0 ± 2%	ASTM D-1653
% SOLIDS BY WEIGHT	67.0 ± 2%	ASTM D-1644
TENSILE STRENGTH	236 ± 50 PSI	ASTM D-2370
ELONGATION	225 ± 25%	ASTM D-2370
PERMEABILITY	20.9 ±3 PERMS	ASTM D-1653
VOC	<50 g Liter	ASTM D-3960-01
VISCOSITY	High	ASTM D-562-01
FLASHPOINT	None	
PH	8.6 - 9.2	ASTM E-70-97
PIGMENT VOLUME	43.0%	
WEIGHT PER GALLON	12 LBS	ASTM D-1475

Meets and exceeds ASTM D6083 requirements.



Corporate Offices: 101 North Prospect Street, Reading, PA 19606 · (866) 273-1355