



Liquid Roofing Products

Liquid Walk Pad

PRODUCT DATA

Description: Acrylabs **Liquid Walk Pad** is a water based, 100% acrylic elastomeric product pre-mixed with rubber granules to provide texture and slip resistance. **Liquid Walk Pad** has been engineered to exhibit excellent elongation, UV resistance and weathering characteristics. The **Liquid Walk Pad** formulation is engineered for excellent adhesion to properly prepared substrates.

Application: **Liquid Walk Pad** is recommended to be roller applied with a ¼" nap roller cover. Cure time varies depending on temperature.

Liquid Walk Pad is available in 5 gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	12.5 LBS	
%SOLIDS BY WEIGHT	69%	
%SOLIDS BY VOLUME	62%	
V.O.C.	<50 g/l	
FLASH POINT	105°F	ASTM D-3278
HARDNESS	50-60	ASTM D-2240
TENSILE STRENGTH	1000 psi	ASTM D-412
ELONGATION	500%	ASTM D-412
REFLECTIVITY	85% (WHITE)	ASTM E-97
WATER ABSORPTION	0.04%	
VAPOR TRANSMISSION	<10 Perms	ASTM D-98G
CURE TIME	12-48 Hours	

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.

Corporate Offices: 101 N. Prospect Street, Reading, PA 19606 · (866) 273-1355